

PRODUCT CODE: 160

D-MAX RUBBER SHIELD LEAK STOPPER - BLACK

DESCRIPTION

DEWITT'S D-MAX RUBBER SHIELD LEAK STOPPER is a rubberized leak sealer that seeps into cracks and holes to seal out air and moisture. When dry, this product is a long-lasting, watertight, paintable, flexible rubber coating that won't sag, drip, crack or peel. Spray this product to stop leaks fast. It is the easy way to coat, seal and protect almost anything. This product dries to a semi-smooth, firm finish that will not sag or drip, and can be top-coated with latex or oil-based paints. This product will be dry-to-the-touch in 25 to 30 minutes.

USES

DEWITT'S D-MAX RUBBER SHIELD LEAK STOPPER is ideal for roof leaks, gutters, skylights, hoses, windowsills, PVC pipes, flashings, duct work, foundations, basements, chimneys, downspouts, vent pipes, A/C drip pans, RVs & campers, trailers and more.

APPLICATION

Ensure that the substrate is free of any dirt or debris. Wash area with a cleaning detergent and water solution, rinse with fresh water, and allow the surface to dry thoroughly. Remove any loose paint or previous coatings with a wire brush or sandpaper. Lightly sand any glossy surfaces. Wipe the sanded surface clean when finished.

- Always use product in a well ventilated are. Best if used at room temperature or in temperatures in excess of 50°F and less than 90°F
- Shake can vigorously before applying to allow the product to fully agitate.
- Hold the can 8 to 10 inches from substrate and apply a nice, even coat. It is best to first apply a light coat. Allow 15 to 20 minutes dry time between coats.
- 2 coats are recommended to properly seal surface. The second coat should always be heavier than the first. Apply more as needed
- Top Coating (Painting) can be performed in 24 hours.



PACKAGING

15 oz aerosol can (Black #160 or White#161)

CAUTION

Combustible: Keep away from heat and open flame. Close container after each use. Keep out of reach of children. Do not induce vomiting. Harmful if swallowed.