



PRODUCT CODE: 407

#10-W SEWER JOINT SEALING COMPOUND

DESCRIPTION

DEWITT'S #10-W SEWER JOINT SEALING COMPOUND is manufactured with special blended asphalts, refined oils, mineral stabilizers and reinforced with hi-tech asbestos-free fibers. DEWITT'S #10-W SEWER JOINT SEALING COMPOUND sets up to form a tough continuous, moisture proof joint that will retain its pliability for a long period of time. This enables it to expand and conform to any movement that might take place. DEWITT'S #10-W SEWER JOINT SEALING COMPOUND adheres to concrete like glue to make a joint that will not leak or infiltrate and is resistant to water, bacteria, and alkali.

USES

DEWITT'S #10-W SEWER JOINT SEALING COMPOUND is compatible with several materials that are used to wrap pipe such as polyester mat, asphalt paper, and some plastics that are compatible with mineral spirits. The material being used should be tested or checked with the manufacturer to see if it is compatible with petroleum solvents.

APPLICATION

DEWITT'S #10-W SEWER JOINT SEALING COMPOUND can be applied directly from the container using a trowel or putty knife. Surfaces must be dry, free of dirt, dust, and debris. Before joining pipe, trowel sufficient compound on entire surface of both tongue and groove so that material will exude on both the inside and outside when pipe is joined. Strike off excess material on inside of line after pipe is joined.

SPECIFICATIONS

Meets ASTM D-217 and Ohio 706-10

PACKAGING

55 gallon drum & 5 gallon pails

CAUTION

Combustible: Keep away from heat and open flame. Close container after each use. Keep out of reach of children. Do not induce vomiting. Harmful if swallowed.



PHYSICAL CHARACTERISTICS

WEIGHT PER GAL (APPROX.)	9 lbs
FLASH POINT (ASTM 093-52)	100° F Min
VISCOSITY AT 80° F	Medium to heavy trowel
SERVICE TEMPERATURE (EXTENDED EXPOSURE)	-40° to 180° F
RESISTANCE TO OILS AND SOLVENTS	Poor
RESISTANCE TO SUNLIGHT AND CHEMICALS	Excellent
RESISTANCE TO ACID, SEWER GAS, BACTERIA, AND WATER	Excellent
RESTRICTIONS	Do not use on tar roofs
CLEAN UP	Mineral Spirits, Naphtha, or DEWITT'S REMOVE-IT

COVERAGE

PIPE SIZE	GAL. PER JOINT	PIPE SIZE	GAL. PER JOINT
8"	1/16 gallon	36"	1 1/8 gallon
12"	1/8 gallon	42"	1 1/2 gallon
15"	3/16 gallon	48"	2 gallons
18"	1/4 gallon	54"	2 3/4 gallons
21"	5/16 gallon	60"	3 1/4 gallons
24"	7/16 gallon	72"	5 gallons
30"	5/8 gallon	84"	9 gallons
33"	3/4 gallon	96"	13 gallons

*The above quantities are for tongue and groove pipe. When Bell and Spigot pipe is used, the above quantities are sufficient if one wrapping of oakum is used to center the pipe. If a wedge is used at the bottom of the pipe instead of oakum, then double the above quantities