



PRODUCT CODE: 511

# DS5000 SUPREME E-Z STIR RUBBERIZED FILLER/SEALER

## DESCRIPTION

DEWITT'S DS5000 SUPREME SEALER with sand is an E-Z STIR formulated, heavy duty asphalt emulsion driveway sealer manufactured by colloidal mill process and fortified with rubber for added pavement adhesion, and non-discoloring graded aggregate for increased traction and longer life. DEWITT'S DS5000 SUPREME SEALER will also fill small voids in asphalt surfaces and has high solids for longer protection.

## USES

DEWITT'S DS5000 SUPREME SEALER may be used with complete confidence on any asphalt pavement. DEWITT'S DS5000 SUPREME SEALER is a continuing maintenance requirement for parking lots, driveways, gasoline stations, school yards, airport runways, or anywhere that the asphalt surface is exposed to gas and oil spillage, extensive abrasion, or weathering.

## APPLICATION

DEWITT'S DS5000 SUPREME SEALER can be applied using a brush, squeegee, roller, or mechanical equipment. Do not apply on rainy, foggy, or extremely humid days or when temperature is expected to drop below 40° F during the next 24 hours. For best results, apply in the AM. Allow at least three months for new asphalt to cure before using DEWITT'S DS5000 SUPREME SEALER. Do not use on concrete.

## SPECIFICATIONS

Meets Federal Specifications RP-355-D

## COVERAGE

One gallon covers 100-125 sq.ft.



## PHYSICAL CHARACTERISTICS

WEIGHT PER GAL (APPROX.)	10 lbs
COLOR	Black
DRYING TIME	24 hours at least
CLEAN UP	Mineral Spirits or DEWITT'S REMOVE-IT
APPLICATION TEMPERATURE	40° F

## PACKAGING

55 gallon drum & 5 gallon pails

## CAUTION

DO NOT ALLOW TO FREEZE. Do not take internally. Close container after each use. Keep out of reach of children. Harmful if swallowed.