

PRODUCT CODE: 618

DS 1500 PLUS DRIVEWAY CRACK FILLER

DESCRIPTION

DEWITT'S DS 1500 PLUS DRIVEWAY CRACK FILLER is a thick blend of asphalt and fillers for heavy duty crack repairs.

USFS

DEWITT'S DS 1500 PLUS DRIVEWAY CRACK FILLER can be used to fill expansion joints and wide cracks, up to one inch wide, or any job requiring a heavy duty crack filler.

APPLICATION

DEWITT'S DS 1500 PLUS DRIVEWAY CRACK FILLER is used directly from the tube. Surface must be free of all dirt, dust, and debris. Keep material in crack and just below the surface. For best results, apply on dry surface when temperature is not expected to drop below 40°F during the next 24 hours. DO NOT APPLY if rain is expected.

SPECIFICATIONS

Meets ASTM D-244, D-977-73, and ASTM M-140-70

COVERAGE

Coverage will vary with size and depth or crack

PACKAGING

10.3 oz cartridges

CAUTION

Combustible: Keep away from heat and open flame. Close container after each use. Keep out of reach of children. Do not induce vomiting. Harmful if swallowed.



PHYSICAL CHARACTERISTICS

WEIGHT PER GAL (APPROX.)	9 lbs
COLOR	Black
DRYING TIME	24 - 48 hours
CLEAN UP	Mineral Spirits or DEWITT'S REMOVE-
APPLICATION TEMPERATURE	Above 40° F